

Accessories

Audible/Visual hi-low temp alarm, standard

- With battery back-up
- With relay for connection to a dialer

Audible/Visual hi-low temp/RH alarm (for chambers with microprocessor-controlled RH only)

Access port, covered, 2" diameter

Access for wiring (Swagelok®)

Clock, digital, to control lights or microprocessor

Coated coil, to resist corrosive vapors

Control panel cover, lockable Plexiglas®

Data pack, mountable stainless steel instrument panel with temperature recorder and standard AV alarm (optional alarm relay)

Door, single-direction mirrored glass

Door, opaque (no light penetration)

Door lock, per hinged door or set of gliding doors

Drawers, stainless steel

- Pull-out
- Two-direction drawers (for pass-thrus)

Exterior light switch

Extra deep cabinet (31" interior/36" exterior), not available in single door sizes

Floor drain, 1.25" diameter

Hot gas bypass (HGBP), single or dual valves

Horizontal air flow ducts

Humidistat-controlled tap water humidity generator, ultrasonic RH

Humidity generator and microprocessor control, available on models with stainless steel or aluminum interior/exterior and hinged doors only. Price includes a switch to turn RH on and off and a HGBP on the compressor. This option will affect the temperature range of the standard model it is added to. Call to verify that the chamber will perform as anticipated.

Humidity meter

Lamp set with two or three lights pigtailed together, one plug, fluorescent or LED

Microprocessor options (not available on standard refrigerators or freezer)

- Retransmit output (0-5, 1-5, 0-10 vDC, or 0-20, 4-20 mAmp)
- RS232 port

Outlet, vapor-proof duplex

Pass-thru options, not available on single-door models

Power switch, key on/off

Remote compressor package

Seismic bolting kit

Shelf, epoxy-coated steel wire, size depends on model: 21" x 17", 24" x 24", 24" x 28", or 24" x 32"

Stainless steel interior or exterior

Stacking kit for undercounter models

Temperature control, multipoint ramp and soak processor

Thermoelectric (Peltier) cooling for some applications

Thermometer, temperature recording, 6" seven day

Thermometer, temp/RH recording, 10" seven day (for chambers with microprocessor-controlled RH only)

Ventilation system, fresh air for plants/animals

Vibration reduction package

Voltage conversions, to 230V/50h, 220V/50h, 220V/60h

Wooden crate, for export

ZNX Temp control for freezer and refrigerators, includes alarm, temp history scroll-back and mini SD data collection



BETATEK INC.

Instrumentation Superbly Supported

L'instrumentation à son meilleur

654 Petrolia Road,
Toronto, ON M3J 2W3
Tel: (416) 736-6166
Toll-Free: (800) 387 3570
Fax: (416) 736-9346