

## -20°C MANUAL DEFROST FREEZER

Packed with enough cooling power to maintain -20° C throughout with  $\pm 2^\circ\text{C}$  temperature uniformity, this 25 ft<sup>3</sup> freezer has six epoxy coated shelves to optimize storage capacity and a digital microprocessor to display the temperature. The chamber is sized to slide through door frames and plugs into a standard wall outlet. A floor drain with tubing attached is included for defrosting. Options such as interior circulating fan for  $\pm 0.5^\circ\text{C}$  uniformity, extra shelves, door lock, hi/low alarm with battery back-up or relay, temperature chart recorder, or stainless steel exterior construction are available.

- Six 28" w x 24" d shelves, epoxy coated
- Microprocessor temp control
- Digital temperature display
- -24° thru 0°C temp range,  $\pm 2^\circ\text{C}$
- Constant temperature cold wall refrigeration system
- Casters, locking, 4"
- Powder coated white or gray steel exterior
- White coated aluminum interior
- Non-CFC foamed insulation
- Self-closing, hinged, solid foamed door
- One year warranty on parts and labor, four add'l years on compressor motor (domestic)



Model	Capacity (ft <sup>3</sup> /liters)	Dimensions		# Shelves and Size	Electrical (domestic)	HP	Ship Weight (lbs/kg)
		Exterior (in/cm)	Interior (in/cm)				
FMS33SD	25/708	33/84 29/74 74.5/189	W D H	29/74 26/66 57.5/146	6 28" x 24"	115/60/1 15 amps	1/2 400/180

Refrigerant is 404A.



**BETATEK** INC.

*Instrumentation Superbly Supported*

*L'instrumentation à son meilleur*

654 Petrolia Road,  
Toronto, ON M3J 2W3  
Tel: (416) 736-6166  
Toll-Free: (800) 387 3570  
Fax: (416) 736-9346