




# NON-REFRIGERATED INCUBATORS

Applications with temperature requirements in the 30-55°C range do not need the refrigeration components on a refrigerated incubator. These heat-only incubators provide temperature control with  $\pm 0.5^\circ\text{C}$  temperature uniformity throughout the chamber. Options such as access ports, A/V alarm, chart reorder and many more are available.

- 30-55°C temperature range
- Digital temperature display, in 0.1°C
- High temperature failsafe
- Double paned hinged (SD) glass doors
- Locking casters, 4"
- Height of chamber sized to fit through doorways
- Cool white LED lighting with interior on/off switch
- Stainless steel interior bottom pan
- Four levels of shelves, adjustable every 1/2"
- Powder coat white, grey or black exterior and white interior finish over steel
- One year parts and labor warranty



Model  
IT70SDINC

Model	Style	Capacity (ft <sup>3</sup> /liters)	Dimensions		# Shelves and Size	# Lights	Electrical (domestic)	Shipping Weight (lbs/kg)
			Exterior (in/cm)	Interior (in/cm)				
IT33SDINC		31/880	33/84	W 29/74	4 28" x 24"	1	115/60/1 15 amps	375/170
			29/74	D 25/64				
			78.5/199	H 69/175				
IT52SDINC		52/1470	52/132	W 48/122	8 24" x 24"	3	115/60/1 15 amps	650/295
			31/79	D 26/66				
			78.5/199	H 69/175				
IT70SDINC		73/2065	70/178	W 66/167	8 32" x 24"	3	115/60/1 15 amps	750/340
			31/79	D 26/66				
			78.5/199	H 69/175				



**BETATEK** INC.

*Instrumentation Superbly Supported*

*L'instrumentation à son meilleur*

654 Petrolia Road,  
Toronto, ON M3J 2W3  
Tel: (416) 736-6166  
Toll-Free: (800) 387 3570  
Fax: (416) 736-9346