


# PASS-THRU PHARMACY REFRIGERATORS

Pass-thru pharmacy refrigerators have sets of doors on both the front and back faces of the chamber. Typically the doors are the hinged type (swinging) which tightly seal in the refrigerated air to help maintain critical temperature uniformity. However, gliding doors offer a space advantage in tight passage ways and are often preferred on one side of the unit. Pass-thru pharmacy refrigerators have a large, easy-to-read digital display. Temperature data is stored on a mini SD card, so the chamber's historical temperature performance can be reviewed graphically. Also, a high/low temperature alarm alerts personnel to temperature excursions (e.g. if the door is left open too long, or a power outage occurs), and the alarm relay can be easily connected to a lab or pharmacy monitoring system. Frequently requested options, such as extra-deep size for 10% more space, stainless steel interior or exterior, trim kit, chart recorder, Swaglok® access port for external alarm sensor and double-direction drawers can be found on our Accessories Sheet.

- 2-10°C temp uniformity
- Microprocessor control with large digital temperature display
- Temperature history "scroll-back" graph
- Mini SD card saves temperature data (downloads to Excel)
- High/Low alarm with relay
- On/off interior light switch for door lights
- Bottom mounted compressor for quiet performance and best energy efficiency
- Stainless steel interior bottom pan to resist corrosion
- Power cord exits through roof of cabinet for safety and security
- One year warranty (P&L), four add'l years on compressor (domestic)



Model PS79SD/SD



Side View

Model*	Style	Capacity (ft <sup>3</sup> /liters)	Dimensions		# Shelves and Size	# Lights	Electrical (domestic)	HP	Shipping Weight (lbs/kg)
			Exterior (in/cm)	Interior (in/cm)					
PS54SD/SDZ		43/1218	54/137	W 48/122	8 24" x 24"	2	115/60/1 20 amps	1/2	625/285
PS54GD/SDZ			31/79	D 26/66					
PS54SD/GDZ			78.5/199	H 57.5/146					
PS72SD/SDZ		59/1670	72/183	W 66/168	8 32" x 24"	2	115/60/1 20 amps	1/2+	800/365
PS72GD/SDZ			31/79	D 26/66					
PS72SD/GDZ			78.5/199	H 57.5/146					
PS79SD/SDZ		63/1780	79/201	W 73/186	12 24" x 24"	4	115/60/1 20 amps	3/4	900/410
PS79GD/SDZ			31/79	D 26/66					
PS79SD/GDZ			78.5/199	H 57.5/146					

\*SD = swinging doors and GD = gliding doors



**BETATEK** INC.

*Instrumentation Superbly Supported*

*L'instrumentation à son meilleur*

654 Petrolia Road,  
Toronto, ON M3J 2W3  
Tel: (416) 736-6166  
Toll-Free: (800) 387 3570  
Fax: (416) 736-9346