

# PHARMACY REFRIGERATORS

Pharmacy Refrigerators have all the features needed to store medicines at the correct temperature. They come with a large digital display for easy reading from afar. Temperature data is stored on a mini SD card, which allows you to review the chamber's historical temperature performance graphically. Also, a high/low temperature alarm alerts personnel to temperature excursions (e.g. if the door is left open too long, or a power outage occurs), and the alarm relay can be easily connected to a lab or pharmacy monitoring system. These refrigerators have glass doors, and the larger (2- and 3-door) models come with your choice of hinged (SD) or gliding (GD) doors. Many options are available including additional shelves, drawers, solid doors, door locks, and full stainless steel construction. Please look over our accessories sheet for a complete listing of available options.

- 2-8°C temp uniformity on single door models
- 2-10°C temp uniformity on two or three door models
- Microprocessor control with large digital temperature display
- Temperature history "scroll-back" graph
- Mini SD card saves temperature data (downloads to Excel)
- High/Low alarm with relay
- Locking casters, 4"
- On/off interior light switch for door lights
- Cool White LED or fluorescent lights
- Stainless steel interior bottom pan to resist corrosion
- Height/depth sized to slide through door frames (without casters)
- One year warranty (P&L), four add'l years on compressor (domestic)



Model	Style	Capacity (ft <sup>3</sup> /liters)	Dimensions		# Shelves and Size	# Lights	Electrical (domestic)	HP	Shipping Weight (lbs/kg)
			Exterior (in/cm)	Interior (in/cm)					
PS26SDZ		10/285	26/66 W 22/56 D 60/152 H	22/56 W 19/48 D 41/104 H	3 21"x17"	1	115/60/1 15 amps	1/5	225/105
PS28SSDZ		24/680	28/71 W 31/79 D 78.5/199 H	24/61 W 29/74 D 57.5/146 H	4 24"x24"	1	115/60/1 15 amps	1/3	375/170
PS33SDZ		27/765	33/84 W 29/74 D 78.5/199 H	29/74 W 27/69 D 57.5/146 H	4 28"x24"	1	115/60/1 15 amps	1/3	400/182
PS52SDZ PS52GDZ		43/1220	52/132 W 31/79 D 78.5/199 H	48/122 W 26/66 D 57.5/146 H	8 24"x24"	2	115/60/1 15 amps	1/3	600/270
PT52SDZ PT52GDZ		52/1470	52/132 W 31/79 D 78.5/199* H	48/122 W 26/66 D 69/175 H	10 24"x24"	2 GD/3 SD	115/60/1 15 amps	1/2	700/318
PS70SDZ PS70GDZ		59/1670	70/178 W 31/79 D 78.5/199 H	66/168 W 26/66 D 57.5/146 H	8 32"x24"	2	115/60/1 20 amps	1/2	800/364
PT70SDZ PT70GDZ		73/2065	70/178 W 31/79 D 78.5/199* H	66/168 W 26/66 D 69/175 H	10 32"x24"	2 GD/3 SD	115/60/1 20 amps	1/2	900/409
PS77SDZ PS77GDZ		63/1780	77/196 W 31/79 D 78.5/199 H	73/186 W 26/66 D 57.5/146 H	12 24"x24"	4	115/60/1 20 amps	1/2	875/398
PT79SDZ PT79GDZ		79/2235	79/201 W 31/79 D 78.5/199* H	73/186 W 26/66 D 69/175 H	15 24"x24"	4	115/60/1 20 amps	1/2+	950/432

\*Denotes irreducible cabinet height. Total height with condensing unit installed and casters installed is 87.75" (223 cm). All models use R-134A as the refrigerant.



**BETATEK** INC.

*Instrumentation Superbly Supported*

*L'instrumentation à son meilleur*

654 Petrolia Road,  
Toronto, ON M3J 2W3  
Tel: (416) 736-6166  
Toll-Free: (800) 387 3570  
Fax: (416) 736-9346