

CI-90

Microbial air sampler - First stainless steel viable sampler with label printer



CI-90/CI-90+ Microbial Air Sampler

First stainless steel viable sampler with label printer.

100 liter per minute flow rate.

Mass flow controller provides optimal sample flow rate for increased accuracy.

Precisely performs a 1 cubic meter sample in 10 minutes (EU GMP Annex 1).

Built-in label printer provides regulatory traceability.

The CI-90 is designed for low particle emissions:

- With filtered exhaust
- Each unit is factory certified for low emissions

Inexpensive operation designed to use industry standard 90 mm petri dish.

Battery provides 7 hours continuous sampling.

The CI-90/CI-90+ incorporates Stainless Steel into critical assemblies for aseptic environments:

- Enclosure
- Sample Head (CI-90 incorporates aluminum sample head)
- Locking Collar

REMOTE SAMPLING? Contact CLiMET to discuss your application.



BETATEK INC.
Instrumentation Superbly Supported
L'instrumentation à son meilleur

654 Petrolia Road,
Toronto, ON M3J 2W3

Tel: (416) 736-6166
Toll-Free: (800) 387 3570
Fax: (416) 736-9346

**Please Contact CLiMET To Arrange For A FREE
Demonstration And Product Information.**

CI-90 SPECIFICATIONS

Sample Lid: CI-90 : Aluminum sampling head. Autoclavable @ 134°C for 20 minutes
CI-90+: Passivated 316 Stainless Steel. Autoclavable @134°C for 20 minutes

Enclosure: 304L Stainless Steel

Sample Flow Rate: 100 liters per minute (0.10 cubic meter or 3.53 cubic feet per minute)

Flow Rate Control: Electronic, automatic closed loop

Battery: Replaceable 9.6 Volts, nickel metal hydride (standard)

Battery Operation Time: 7 hours of continuous operation

Time To Charge Battery: 2.0 to 2.5 hours (internal charger)

Display: 4x20 character LCD

Printer: Thermal, prints on 5/8" tall by 2" wide thermal adhesive labels

Unit ID: User selectable; 6 characters long

User ID: Up to 10 users; 9 characters long

Security: Security to prevent settings changes or stopping of sampling

Location ID: Up to 100; 15 characters long

Input/Output: RS-232

Audible Alarm: Built-in

Alarm Limits: +/- 10% deviation from 100LPM flow rate

Dimensions: H-W-D: 7.5 X 8.1 X 9.9 inches (19.0 X 20.6 X 25.1 cm)

Weight: CI-90 : 10.5 lb (4.77 Kg) with battery
CI-90+ : 12 lb (5.45 Kg) with battery

Power: Auto Switching: 100–240 VAC, 50/60 Hz

Operating Range: 32 - 97°F (0 - 36°C), 10–90% RH, non-condensing

Calibration: Factory prime calibration of flow system accuracy

Calibration Frequency: Recommended every 12 months



BETATEK INC.
Instrumentation Superbly Supported
L'instrumentation à son meilleur

654 Petrolia Road,
Toronto, ON M3J 2W3

Tel: (416) 736-6166
Toll-Free: (800) 387 3570
Fax: (416) 736-9346

CLIMET®
CLIMET INSTRUMENTS COMPANY

1320 West Colton Avenue • Redlands, California 92374
Telephone: (909) 793-2788 • Facsimile: (909) 793-1738
Email: sales@climet.com • www.climet.com

PLEASE CONTACT CLIMET TO ARRANGE FOR A FREE DEMONSTRATION AND PRODUCT INFORMATION.