

Humidified Incubators

If your research requires warm temperatures, controlled additive humidity (greater than room ambient), and little or no light - these chambers may meet your needs. With an operating temperature range of 20-50°C, ±1°C measured at the sensor, and ultrasonic humidity generation using tap or RO water, these chambers provide the perfect environment for a wide range of uses, including ninhydrin testing, drywall (gypsum) stability, cement curing stability, and product/packaging shelf life testing. Chamber conditions are monitored and displayed digitally on twin microprocessors. Air flows vertically up through the shelves, and interior lighting allows viewing or product identification through the glass doors. The rugged stainless steel cabinet rolls easily on casters. To customize this product, select options from the accessories sheet to augment these features:

- ~ 20-50°C temperature range, digital temperature display, in 0.1°C
- ~ High temperature failsafe
- ~ Microprocessor controlled additive ultrasonic RH
- ~ Floor drain
- ~ Stainless steel interior and exterior
- ~ Double pane hinged glass doors, heated
- ~ Locking casters, 4"
- ~ Height of chamber sized to fit through doorways
- ~ Cool white LED lighting with interior on/off switch
- ~ Bottom mounted condensing units (quiet operation)
- ~ Shelves are adjustable every 1/2"
- ~ Shelves are epoxy coated steel wire capable of holding 125 lbs (57 kg)
- ~ One year parts and labor warranty
- ~ Four additional years on the compressor (part only)



Model HIS33SD

Model	Style	Capacity (ft ³ /liters)	Dimensions		# Shelves and Size	# Lights	Electrical (domestic)	HP	Shipping weight (lbs/kg)
			Exterior* (in/cm)	Interior (in/cm)					
HIS26SD		10/285	26/66	W 22/56	3 21" x 17"	1	115/60/1 15 amps	1/5	250/115
			22/56	D 19/48					
			60/152	H 41/104					
HIS28SSD		24/680	28/71	W 24/61	4 24" x 24"	1	115/60/1 5-20P	1/3	450/205
			31/79	D 29/74					
			78.5/199	H 57.5/146					
HIS33SD		27/765	33/84	W 29/74	4 28" x 24"	1	115/60/1 5-20P	1/3	450/205
			29/74	D 27/69					
			78.5/199	H 57.5/146					
HIS52SD		43/1220	52/132	W 48/122	8 24" x 24"	2	115/60/1 L5-30P	1/3	675/305
			31/79	D 26/66					
			78.5/199	H 57.5/146					

*Excluding Casters



BETATEK INC.

Instrumentation Superbly Supported

L'instrumentation à son meilleur

654 Petrolia Road,
Toronto, ON M3J 2W3
Tel: (416) 736-6166
Toll-Free: (800) 387 3570
Fax: (416) 736-9346