

-20°C Manual Defrost Freezer

Packed with enough cooling power to maintain -20°C throughout with $\pm 2^\circ\text{C}$ temperature uniformity, this 25 ft³ freezer has six epoxy coated shelves to optimize storage capacity and a digital microprocessor to display the temperature. The chamber is sized to slide through door frames and plugs into a standard wall outlet. A floor drain with tubing attached is included for defrosting. Options such as interior circulating fan for $\pm 0.5^\circ\text{C}$ uniformity, extra shelves, door lock, hi/low temperature alarm with battery back-up or relay, temperature chart recorder, or stainless steel exterior construction are available.

- ~ Six 28" w x 24" d shelves, epoxy coated
- ~ Microprocessor temperature control
- ~ Digital temperature display
- ~ -24° through 0°C temperature range, $\pm 2^\circ\text{C}$
- ~ Constant temperature cold wall refrigeration system
- ~ Casters, locking, 4"
- ~ Powder coated white or gray steel exterior
- ~ White coated aluminum interior
- ~ Non-CFC foamed insulation
- ~ Self-closing, hinged, solid foamed door
- ~ One year warranty on parts and labor, four additional years on compressor motor (domestic)



Model
FMS33SD

Model	Capacity (ft ³ /liters)	Dimensions		# Shelves and Size	Electrical (domestic)	HP	Ship Weight (lbs/kg)
		Exterior (in/cm)	Interior (in/cm)				
FMS33SD	25/708	33/84	W 29/74	6 28" x 24"	115/60/1 15 amps	1/2	450/205
		29/74	D 26/66				
		74.5/189	H 57.5/146				

Refrigerant is 404A.



BETATEK INC.

Instrumentation Superbly Supported

L'instrumentation à son meilleur

654 Petrolia Road,
Toronto, ON M3J 2W3
Tel: (416) 736-6166
Toll-Free: (800) 387 3570
Fax: (416) 736-9346