





# Non-Refrigerated Incubators

Applications with temperature requirements in the 30-60°C range do not need the refrigeration components on a refrigerated incubator. These heat-only incubators provide temperature control with  $\pm 0.5^\circ\text{C}$  temperature uniformity throughout the chamber. Options such as access ports, A/V alarm, chart recorder and many more are available.

- ~ 30-50°C temperature range, with optional exterior-mounted fan motor available for 50-60°C operation
- ~ Digital temperature display, in 0.1°C
- ~ High temperature failsafe
- ~ Double paned hinged (SD) glass doors
- ~ Locking casters, 4"
- ~ Height of chamber sized to fit through doorways
- ~ Cool white LED lighting with interior on/off switch
- ~ Stainless steel interior bottom pan
- ~ Four levels of shelves, adjustable every 1/2"
- ~ Powder coat white, grey or black exterior and white interior finish over steel
- ~ One year parts and labor warranty



Model IT70SDINC

| Model     | Style   | Capacity<br>(ft <sup>3</sup> /liters) | Dimensions          |                     | # Shelves<br>and Size | # Lights | Electrical<br>(domestic) | Shipping Weight<br>(lbs/kg) |
|-----------|---|---------------------------------------|---------------------|---------------------|-----------------------|----------|--------------------------|-----------------------------|
|           |   |                                       | Exterior<br>(in/cm) | Interior<br>(in/cm) |                       |          |                          |                             |
| IT26SDINC |  | 10/285                                | 26/66               | W 22/56             | 3<br>21" x 17"        | 1        | 115/60/1<br>15 amps      | 250/115                     |
|           |   |                                       | 22/56               | D 19/48             |                       |          |                          |                             |
|           |   |                                       | 60/152              | H 41/104            |                       |          |                          |                             |
| IT33SDINC |  | 31/880                                | 33/84               | W 29/74             | 4<br>28" x 24"        | 1        | 115/60/1<br>15 amps      | 425/195                     |
|           |   |                                       | 29/74               | D 25/64             |                       |          |                          |                             |
|           |   |                                       | 78.5/199            | H 69/175            |                       |          |                          |                             |
| IT52SDINC |  | 52/1470                               | 52/132              | W 48/122            | 8<br>24" x 24"        | 3        | 115/60/1<br>15 amps      | 700/320                     |
|           |   |                                       | 31/79               | D 26/66             |                       |          |                          |                             |
|           |   |                                       | 78.5/199            | H 69/175            |                       |          |                          |                             |
| IT70SDINC |  | 73/2065                               | 70/178              | W 66/167            | 8<br>32" x 24"        | 3        | 115/60/1<br>15 amps      | 800/365                     |
|           |   |                                       | 31/79               | D 26/66             |                       |          |                          |                             |
|           |   |                                       | 78.5/199            | H 69/175            |                       |          |                          |                             |



**BETATEK** INC.

*Instrumentation Superbly Supported*

*L'instrumentation à son meilleur*

654 Petrolia Road,  
Toronto, ON M3J 2W3  
Tel: (416) 736-6166  
Toll-Free: (800) 387 3570  
Fax: (416) 736-9346