

# Pharmacy Refrigerators

Pharmacy Refrigerators have all the features needed to store medicines at the correct temperature. They come with a digital display for easy reading. The high/low temperature alarm alerts personnel to temperature excursions (e.g., if the door is left open too long or a power outage occurs), and the alarm has 2 sensors - one to measure the actual air fluctuations and one to reflect the vaccine temperature. Also, the cooling coils are electrofin coated to protect them from some types of harsh sanitizers. These refrigerators have glass doors, and the larger (2 and 3-door) models come with your choice of hinged (SD) or gliding (GD) doors. Many options are available including additional shelves, drawers, solid doors, door locks, and full stainless steel construction. Please look over our accessories sheet for a complete listing of available options.

- ~ 2-8°C temperature uniformity on single door models
- ~ 2-10°C temperature uniformity on two or three door models
- ~ Microprocessor control with digital temperature display
- ~ Electrofin coated cooling coils
- ~ High/low temperature alarm with two sensors (weighted and non-weighted)
- ~ Locking casters, 4"
- ~ On/off interior light switch for door lights
- ~ Cool white LED lights
- ~ Stainless steel interior bottom pan to resist corrosion
- ~ Height/depth sized to slide through door frames (without casters)
- ~ One year warranty (P&L), four additional years on compressor (domestic)



Model	Style	Capacity (ft <sup>3</sup> /liters)	Dimensions		# Shelves and Size	# Lights	Electrical (domestic)	HP	Shipping Weight (lbs/kg)
			Exterior (in/cm)	Interior (in/cm)					
PS26SDA		10/285	26/66	W 22/56	3 21"x17"	1	115/60/1 15 amps	1/5	275/125
			22/56	D 19/48					
			56/142	H 41/104					
PS28SSDA		24/680	28/71	W 24/61	4 24"x24"	1	115/60/1 15 amps	1/3	400/180
			31/79	D 29/74					
			74.5/189	H 57.5/146					
PS33SDA		27/765	33/84	W 29/74	4 28"x24"	1	115/60/1 15 amps	1/3	425/195
			29/74	D 27/69					
			74.5/189	H 57.5/146					
PS52GDA PS52SDA		43/1220	52/132	W 48/122	8 24"x24"	2 GD/3 SD	115/60/1 15 amps	1/3	575/260
			31/79	D 26/66					
			74.5/189	H 57.5/146					
PT52GDA PT52SDA		52/1470	52/132	W 48/122	10 24"x24"	2 GD/3 SD	115/60/1 15 amps	1/2	650/295
			31/79	D 26/66					
			74.5/189*	H 69/175					
PS70GDA PS70SDA		59/1670	70/178	W 66/168	8 32"x24"	2 GD/3 SD	115/60/1 15 amps	1/2	720/325
			31/79	D 26/66					
			74.5/189	H 57.5/146					
PT70GDA PT70SDA		73/2065	70/178	W 66/168	10 32"x24"	2 GD/3 SD	115/60/1 15 amps	1/2	800/365
			31/79	D 26/66					
			74.5/189*	H 69/175					
PS77GDA PS77SDA		63/1780	77/196	W 73/186	12 24"x24"	4	115/60/1 15 amps	1/2	770/350
			31/79	D 26/66					
			74.5/189	H 57.5/146					
PT77GDA PT77SDA		79/2235	77/196	W 73/186	15 24"x24"	4	115/60/1 15 amps	1/2	850/385
			31/79	D 26/66					
			74.5/189*	H 69/175					

\*Denotes irreducible cabinet height. Total height with condensing unit installed and casters installed is 87.75" (223 cm).



**BETATEK** INC.

*Instrumentation Superbly Supported*

*L'instrumentation à son meilleur*

654 Petrolia Road,  
Toronto, ON M3J 2W3  
Tel: (416) 736-6166  
Toll-Free: (800) 387 3570  
Fax: (416) 736-9346