

Non-Refrigerated Incubators

Applications with temperature requirements in the 30–60°C range do not need the refrigeration components on a refrigerated incubator. These heat-only incubators provide temperature control with $\pm 0.5^\circ\text{C}$ temperature uniformity throughout the chamber. Options such as access ports, A/V alarm, chart recorder and many more are available.

- ~ 30–50°C temperature range, with optional exterior-mounted fan motor available for 50–60°C operation
- ~ Digital temperature display, in 0.1°C
- ~ High temperature failsafe
- ~ Double paned hinged (SD) glass doors
- ~ Locking casters, 4"
- ~ Height of chamber sized to fit through doorways
- ~ Cool white LED lighting with interior on/off switch
- ~ Stainless steel interior bottom pan
- ~ Four levels of shelves, adjustable every $1/2"$
- ~ Powder coat white, grey or black exterior and white interior finish over steel
- ~ One year parts and labor warranty



Model IT70SDINC

Model	Style	Capacity (ft ³ /liters)	Dimensions		# Shelves and Size	# Lights	Electrical (domestic)	Shipping Weight (lbs/kg)
			Exterior (in/cm)	Interior (in/cm)				
IS26SDINC		10/285	26/66	W 22/56	3 21" x 17"	1	115/60/1 15 amps	250/115
			22/56	D 19/48				
			60/152	H 41/104				
IT33SDINC		31/880	33/84	W 29/74	4 28" x 24"	1	115/60/1 15 amps	425/195
			29/74	D 25/64				
			78.5/199	H 69/175				
IT52SDINC		52/1470	52/132	W 48/122	8 24" x 24"	3	115/60/1 15 amps	700/320
			31/79	D 26/66				
			78.5/199	H 69/175				
IT70SDINC		73/2065	70/178	W 66/167	8 32" x 24"	3	115/60/1 15 amps	800/365
			31/79	D 26/66				
			78.5/199	H 69/175				



BETATEK INC.
Instrumentation Superbly Supported
L'instrumentation à son meilleur

654 Petrolia Road,
Toronto, ON M3J 2W3

Tel: (416) 736-6166
Toll-Free: (800) 387 3570
Fax: (416) 736-9346