



Thermostatic Water Bath

BMP 30



Specially designed for serology

Ideal for modern laboratories, our serological bath is available in 2 volumes; 3 and 6 litres, and consists of a transparent plexiglass and a control interface via a button. This makes it very easy to use and set the ambient temperature between 7°C to 60°C.

TECHPERFORMANCE


Ambient temperature range	7°C to 60°C
Factory preset	37°C and 56°C
Capacity	3L

SHELFWARRANTY

Parts	2 years
-------	---------



Water lack safety



Available in 2 volumes



BETATEK INC.
Instrumentation Superbly Supported
L'instrumentation à son meilleur

654 Petrolia Road,
 Toronto, ON M3J 2W3
 Tel: (416) 736-6166
 Toll-Free: (800) 387 3570
 Fax: (416) 736-9346

Technical Specifications

SEROLOGIC WATER BATH	
MODEL	BMP 30
GENERAL SPECIFICATIONS	
Capacity (net)	3 litres
Temperature Range (ambient)	7°C to 60°C
Construction	Polycarbonate frame
External Dimensions (W x H x D)	360 x 120 x 130 mm
Internal Dimensions (W x H x D)	280 x 110 x 80 mm
Weight (gross)	3kg
Weight (net)	1.5kg
Factory Setpoint	37°C and 56°C
Water lack safety	Yes
Warranty	2 years
ELECTRICAL DATA	
Power supply	230V ~ +/-10%, 50 Hz
Energy consumption	250 W
COMPLIANCE	
Device complies with CE specifications	
OPTIONS	
Polycarbonate lid	
1 rack for 60 tubes diam. 14mm	
Thermometer	

* Cleaning and decontamination with detergents and antimicrobials used in hospitals (Ammonium quaternary / except pure bleach)



Thermostatic Water Bath

BMP 60



Specially designed for serology

Ideal for modern laboratories, our serological bath is available in 2 volumes; 3 and 6 litres, and consists of a transparent plexiglass and a control interface via a button. This makes it very easy to use and set the ambient temperature between 7°C to 60°C.

TECHPERFORMANCE


Ambient temperature range	7°C to 60°C
Factory preset	37°C and 56°C
Capacity	6L

3-YEAR WARRANTY

Parts	2 years
-------	---------



Water lack safety



Available in 2 volumes



BETATEK INC.
Instrumentation Superbly Supported
L'instrumentation à son meilleur

654 Petrolia Road,
 Toronto, ON M3J 2W3
 Tel: (416) 736-6166
 Toll-Free: (800) 387 3570
 Fax: (416) 736-9346

Technical Specifications

SEROLOGIC WATER BATH	
MODEL	BMP 60
GENERAL SPECIFICATIONS	
Capacity (net)	6 liters
Temperature Range (ambient)	7°C to 60°C
Construction	Polycarbonate frame
External Dimensions (W x H x D)	370 x 150 x 210 mm
Internal Dimensions (W x H x D)	290 x 110 x 190 mm
Weight (gross)	4kg
Weight (net)	2kg
Factory Setpoint	37°C and 56°C
Water lack safety	Yes
Warranty	2 years
ELECTRICAL DATA	
Power supply	230V ~ +/-10%, 50 Hz
Energy consumption	250 W
COMPLIANCE	
Device complies with CE specifications	
OPTIONS	
Polycarbonate lid	
2 racks for 60 tubes diam. 14mm	
Thermometer	

* Cleaning and decontamination with detergents and antimicrobials used in hospitals (Ammonium quaternary / except pure bleach)